

FEATURES:

- Special Design Available
- Low Current Requirements
- High Light Output
- Easy Key Code

ABSOLUTE MAXIMUM RATINGS, $T_a = 25^\circ\text{C}$

Reverse voltage per led chip.....	5.0 V
D.C Forward current per led chip.....	30 mA
Pulse current. (1.10 duty cycle , 0.1 ms pulse width) per led chip.....	100mA
Operating temperat. range.....	-25 $^\circ\text{C}$ to + 85 $^\circ\text{C}$
Storage temperat. range.....	-25 $^\circ\text{C}$ to + 100 $^\circ\text{C}$
Lead soldering temp.	260 $^\circ\text{C}$ for 5 seconds

ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ\text{C}$

PART NUMBER COMMON CATHODE	PART NUMBER COMMON ANODE	LED CHIP MATERIAL	LED CHIP EMITT. COLOR	SURFACE COLOR	SEGM. OR DOT COLOR	PEAK WAVE LENG. 20mA	FORWARD VOLTAGE Vf 20mA (V) TIP MAX	LUMIN. INTENS. 10 mA (mcd) MIN TYP
OPD 801HR2CGW-1	OPD 801HR2AGW-1	GaAsP GaP	HI RED	GRAY	WHITE	635	1.8 2.3	2.2 2.6
OPD 801SR3CGW-1	OPD 801SR3AGW-1	GaAlS GaAs	SUPER RED	GRAY	WHITE	660	1.8 2.4	5.8 6.4
OPD 801G1CGW-1	OPD 801G1AGW-1	GaP	GREEN	GRAY	WHITE	570	2.1 2.8	1.8 2.3
OPD 801O2CGW-1	OPD 801O2AGW-1	GaAsP GaP	ORANGE	GRAY	WHITE	630	2.0 2.8	2.2 2.6

*SPECIFICATIONS ARE SUBJECT TO CHANGE

*THE PN s ABOVE MEANS STANDART VERSION, (SURFACE GRAY AND WHITE SEGMENT)

NOTE: ALL DIMENSIONS ARE IN mm, TOLERANCE IS +/-0.25mm, UNLESS OTHERWISE NOTED. THE SLOPE ANGLE OF ANY PIN MAY BE +/- 5.0 MAX.

PACKAGE DIMENSIONS AND PIN FUNCTION

