

FEATURES:

- Special Design Available
- Low Current Requirements
- High Light Output
- Easy Key Code

ABSOLUTE MAXIMUM RATINGS, $T_a = 25^\circ\text{C}$

Reverse voltage per led chip.....	5.0 V
D.C Forward current per led chip.....	30 mA
Pulse current. (1.10 duty cycle , 0.1 ms pulse width) per led chip	100mA
Operating temperat. range.....	-25 $^\circ\text{C}$ to + 85 $^\circ\text{C}$
Storage temperat. range	-25 $^\circ\text{C}$ to + 100 $^\circ\text{C}$
Lead soldering temp.	260 $^\circ\text{C}$ for 5 seconds

ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ\text{C}$

PART NUMBER COMMON CATHODE	PART NUMBER COMMON ANODE	LED CHIP MATERIAL	LED CHIP EMITT. COLOR	SURFACE COLOR	SEGM. OR DOT COLOR	PEAK WAVE LENG. 20mA	FORWARD VOLTAGE Vf 20mA (V) TIP MAX	LUMIN. INTENS. 10 mA (mcd) MIN TYP
OPD 404HR2MCGW	OPD 404HR2MAGW	GaAsP GaP	HI RED	GRAY	WHITE	635	1.8 2.3	1.8 2.4
OPD 404SR3MCGW	OPD 404SR3MAGW	GaAlAs GaAs	SUPER RED	GRAY	WHITE	660	1.8 2.4	5.0 6.0
OPD 404G1MCGW	OPD 404G1MAGW	GaP	GREEN	GRAY	WHITE	570	2.1 2.8	1.8 2.3
OPD 404O2MCGW	OPD 404O2MAGW	GaAsP GaP	ORANGE	GRAY	WHITE	630	2.0 2.8	1.8 2.4

*SPECIFICATIONS ARE SUBJECT TO CHANGE

*THE PN s ABOVE MEANS STANDART VERSION, (SURFACE GRAY AND WHITE SEGMENT).

NOTE: ALL DIMENSIONS ARE IN mm, TOLERANCE IS +/-0.25mm, UNLESS OTHERWISE NOTED. THE SLOPE ANGLE OF ANY PIN MAY BE +/- 5.0

PACKAGE DIMENSION

