

FEATURES:

- Special Design Available
- Low Current Requirements
- High Light Output
- Easy Key Code

ABSOLUTE MAXIMUM RATINGS, $T_a = 25^\circ\text{C}$

Reverse voltage per led chip.....	5.0 V
D.C Forward current per led chip.....	30 mA
Pulse current. (1.10 duty cycle , 0.1 ms pulse width) per led chip.....	100mA
Operating temperat. range.....	-25 $^\circ\text{C}$ to + 85 $^\circ\text{C}$
Storage temperat. range.....	-25 $^\circ\text{C}$ to + 100 $^\circ\text{C}$
Lead soldering temp.	260 $^\circ\text{C}$ for 5 seconds

ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ\text{C}$

PART NUMBER	LED CHIP MATERIAL	LED CHIP EMITT. COLOR	SURFACE COLOR	SEGM. OR DOT COLOR	PEAK WAVE LENG. 20mA	FORWARD VOLTAGE Vf 20mA (V) TYP. MAX.	LUMIN. INTENS. 10 mA (mcd) TYP. MIN.
OPM 757HR2CGW	GaAsP GaP	HI RED	GRAY	WHITE	635	1.8 2.3	2.5 3.5
OPM 757SR3CGW	GaAlAs GaAS	SUPER RED	GRAY	WHITE	660	1.8 2.3	2.3 5.9
OPM 757G1CGW	GaP	GREEN	GRAY	WHITE	570	2.2 2.5	2.0 2.5
OPM 757O2CGW	GaAsP GaP	ORANGE	GRAY	WHITE	630	2.0 2.5	2.0 2.5

*SPECIFICATIONS ARE SUBJECT TO CHANGE

*THE PN s ABOVE MEANS STANDART VERSION, (SURFACE GRAY AND WHITE SEGMENT).

NOTE: ALL DIMENSIONS ARE IN mm, TOLERANCE IS +/-0.25mm, UNLESS OTHERWISE NOTED. THE SLOPE ANGLE OF ANY PIN MAY BE +/- 5.0 MAX.

PACKAGE DIMENSIONS AND PIN FUNCTION

