

FEATURES:

- Special Design Available
- Low Current Requirements
- High Light Output
- Easy Key Code

ABSOLUTE MAXIMUM RATINGS, $T_a = 25^\circ C$

Reverse voltage per led chip.....	5.0 V
D.C Forward current	30 mA
Pulse current. (1.10 duty cycle , 0.1 ms pulse width)	100mA
Operating temperat. range.....	-25°C to + 85°C
Storage temperat. range.....	-25°C to + 100°C
Lead soldering temp.	260°C for 5 seconds

ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ c$

PART NUMBER	LED CHIP MATERIAL	LED CHIP EMITT. COLOR	SURFACE COLOR	SEGM. OR DOT COLOR	PEAK WAVE LENG. 20mA (nm)	FORWARD VOLTAGE Vf 20mA (V) TYP. MAX.	LUMIN. INTENS. 10 mA (mcd) TYP.
OPM 1988G1CGW	GaP	GREEN	GRAY	WHITE	570	2.2 2.5	2.5
OPM 1988HR2CGW	GaAsP GaP	HI-RED	GRAY	WHITE	660	1.8 2.3	3.5
OPM 1988SR3CGW	GaAlAs GaAs	SUPER RED	GRAY	WHITE	660	1.8 2.3	6.0

*SPECIFICATIONS ARE SUBJECT TO CHANGE

*THE PIN S ABOVE MEANS STANDART VERSION, (SURFACE GRAY AND WHITE SEGMENT).

NOTE: ALL DIMENSIONS ARE IN mm, TOLERANCE IS +/- 0.25mm, UNLESS OTHERWISE NOTED. THE SLOPE ANGLE OF ANY PIN MAY BE +/- 5.0 MAX.

PACKAGE DIMENSIONS AND PIN FUNCTION

